




Semi-Automatic Tape Sealer
Up to 30 cases per minute



RSC Case
The BEL 130
seals RSC
cases.

Quick Change Semi-Automatic Case Sealer



Easy Case Change

Size changes on the BEL 130 are fast and effortless. A self-centering width adjustment and counter-balanced upper assembly with a single lever clamp reduces size changes to seconds.



Superior Tape Application

The BEL 130 is equipped with state-of-the-art DEKKA High Performance plated steel tape heads that are easily loaded in or out of the machine in 30 seconds or less.



Case Sealer

BEL 130

BEL 130 Quick Change Semi-Automatic Case Taper

BEL 130 Features

- Slim profile, heavy gage welded structural tube frame enables easy access to bottom tape head
- Tough epoxy powder coating resists chipping and flaking
- One piece modular design drive system is easily removed from machine frame for convenient bench service
- Magnetic Motor Starter (oil and dust tight)
- DEKKA's exclusive "No Break" tape feed delivers reliable performance with all brands and grades of pressure sensitive tape. The DEKKA head is especially forgiving when applying light weight, lower cost tapes
- Standard DEKKA 02 Plated Steel 2" (51mm) tape heads and optional DEKKA 22 Stainless Steel 2" tape heads

Complete Solution



BEL505 Case Former

The BEL 505 improves efficiency and ergonomics. Inserting a case into the BEL 505 results in all four bottom flaps being automatically folded, leaving hands free to pack.



A32 Accumulation Table


Rotary turntable that presents product to the operator for packing. Features an adjustable speed motor.



KDF Box Stand

Height adjustable stand for holding case blanks and keeping them off the floor. Speeds up productivity by positioning case blanks conveniently to the operator.

How the BEL 130 Works



RSC Case
The BEL 130 seals RSC cases.




1 Height Adjustment

Upper assembly is adjusted with a single lever clamp which increases or reduces size in seconds.



2 Width Adjustment

The self centering width adjustment is effortless.



3 Top & Bottom Sealed

Superior case sealing performance is achieved with its quality tape application. The BEL 130 comes standard with DEKKA tape heads.

BEL 130 Specifications

Case Size Range	Length	Width	Height
Minimum	6" 152 mm	5" 127 mm	3 1/2" 89 mm
Maximum	unlimited	20" 508 mm	20" 508 mm
Infeed/Outfeed Height			
Minimum	21 1/2" (546 mm) with pads		
Maximum	33 1/2" (851 mm) with pads		
Machine Speed: Up to 30 cases per minute depending on box size.			

* Specifications are subject to change without notice.



Wexxar Packaging Inc.
10101 Nordel Court
Delta, BC Canada
V4G 1J8

Phone: 604-930-9300
Fax: 604-930-9368
Email: sales@wexxar.com
Web: www.wexxar.com

a division of Pro Mach 

Backed by Wexxar's warranty and experienced, nationwide service team.