




Random Semi-Automatic Tape Sealer
Up to 20 cases per minute



RSC Case
The BEL 185
seals RSC
cases.

Random Semi-Automatic Case Sealer

The innovative BEL 185 Semi-Automatic Random sealer self-adjusts and applies pressure-sensitive tape, top and bottom, to random and uniform size cartons, eliminating the need for manual adjustments, and resulting in improved productivity on case sealing lines.

The BEL 185 allows one person to coordinate the sealing of various sizes of corrugated cases into a single operation. The BEL 185 easily and safely converts to a fixed position sealer for maximum throughput of uniform case sizes.

The engineered performance and unique safety provisions of the BEL 185 offer superior operator comfort and increased productivity, sealing up to 25 cases per minute.

The compact, easy to operate BEL 185 automates random case applications, simplifying sealing and improving efficiency on multiple size case packing lines. The self-adjusting BEL 185 offers quick, safe transitions from one case size to another - freeing the operator of time-consuming manual adjustments.

BEL 185 Case Sealer

BEL 185 Random Semi-Automatic Case Taper

BEL 185 Features

- Compact Design
- The self adjustable minimum/maximum settings for case width and height parameters provides higher production rates
- Longer machine life and superior performance assured with a heavy duty, welded steel frame
- Powder coating, zinc plated finishes, and stainless steel components offer environmental protection
- The force-sensitive side guide rails and the extended height “sensor” provide a new level of safety
- Reliable, consistent tape application provided by the exclusive “no break” tape advance with DEKKA high performance tape heads

Complete Solution



BEL 185SS Stainless Steel Case Taper
The stainless steel option is available for washdown environments.



A32 Accumulation Table
Rotary turntable that presents product to the operator for packing. Features an adjustable speed motor.


BEL 185 Specifications

Case Size Range	Length	Width	Height
Minimum	8" 203 mm	6" 152 mm	4 1/2" 114 mm
Maximum	unlimited	20" 507 mm	19 1/2" 495 mm
Infeed/Outfeed Height (with adjustable foot pads)			
Minimum	25" (635 mm)		
Maximum	28" (711 mm)		
Tape Heads: DEKKA 22 model - 2" (51 mm) or optional DEKKA 23 model - 3" (76 mm)			
Machine Speed: Up to 20 cases per minute			

* Specifications are subject to change without notice.

How the BEL 185 Works

RSC Case
The BEL 185 seals RSC cases.



1 Quick Set Up

Upper assembly is set to the largest case size with a simple hand wheel adjustment.



2 Self Adjusting Tape Mast

The tape mast and side guide rails adapt from one box to another, quickly adjusting for various box sizes.



3 Top & Bottom Sealed

Superior case sealing performance is achieved with its quality tape application. The BEL 185 comes standard with DEKKA tape heads.



Wexxar Packaging Inc.
10101 Nordel Court
Delta, BC Canada
V4G 1J8

Phone: 604-930-9300
Fax: 604-930-9368
Email: sales@wexxar.com
Web: www.wexxar.com

a division of Pro Mach 

Backed by Wexxar's warranty and experienced, nationwide service team.