

For more information: S www.neffpack.com

1(800)827-5220

sales@neffpack.com

## **THE 2100-SRT STRETCH WRAP MACHINE** Control panel with simple LCD operator interface Carriage cable wires not exposed including helpful diagnostics Super Rapid Thread II powered pre-stretch film carriage uses less film Less film slippage means more All motors/gearboxes consistent stretch and the "sticky" fully enclosed & guarded side of the film will always be against both the rubber rollers and the load where it belongs All AC Motors Lifting Tubes - front and rear for easy portability 4000lbs load capacity Heavy-Duty surround deck

The 2100-SRT - More Features, More Benefits! Built in North America with Brand Name Components

# 2100-SRT DESIGN FEATURES/SPECIFICATIONS

1

SWITC

6

#### LOAD CAPACITY

- 50" L x 50" W x 80" H
- 4000# turntable capacity
- **NOTE:** Larger load size options are available.

#### CONTROLS

- LCD Operator Interface with Diagnostics
- Cycle Pause & Reinforce Wrap
- Separate UP/DOWN Spiral Speed Controls
- NEMA 12 with Emergency Stop Button
- 3 Separate Wrap Programs
- Selectable Reduced Film Tension parameters
- for wrapping top and/or bottom of light loads
- 115 Volts 1 Phase 60 Hz 15 Amps
- 3 Year Warranty on Components

### **FILM CARRIAGE**

- Super Rapid Thread II ™ 20" capacity pre-stretch film carriage
  Safety Door with auto power cut-off switch
- Special Film Threading Device Uniquely orientates the sticky side of the film against the pre-stretch rollers and the inside on the load.
- ½ HP AC variable speed motor
- 33% to 313% fixed stretch capability
- Carriage Descent Safety Shut-Off Device
- Superior film-to-roller contact area
- Lifetime warranty on pre-stretch rollers

#### **TOWER DESIGN**

- Fully Enclosed & Guarded Motors
- No Éxposed Cables
- Heavy Duty Formed/Structural Steel
  Electro-static powder coated paint finish
- 5 Year Warranty on Steel Fabrications

#### TURNTABLE

- 4000# capacity with Heavy Duty Surround deck
- 1 12 RPM with Soft Start Acceleration
- ½ HP AC Variable Speed Drive
- Forklift Tubes Front and Rear
- Maintenance Free 42 Support Wheels
- 🔷 57" diameter
- Optional loading ramp 60" long x 48" wide complete with 10" level porch area available

GING SYSTEMS



A Proud Distributor of PACKAGING INC equipment